

Fire Extinguishers

Fire Classification

- Class A Fires - Ordinary combustibles such as wood, cloth, paper, straw and stalks
- Class B Fires - Flammable liquids, gases and greases
- Class C Fires - Energized electrical fires

ABC Fire Extinguishers

- Specially formulated ammonium phosphate-base dry chemical extinguishers may be effectively used to combat Class A and Class B fires as well as having a Class C listing
- Allows use in the presence of energized electrical equipment
- Designed and engineered to the highest-quality standards
- Meets DOT, Coast Guard and OSHA requirements
- Operating temperature: -65° F to 120° F
- Operating range: 2-1/2 lb. (9 to 15 ft.), 5 lb. (12 to 18 ft.), 10 and 20 lb. (15 to 21 ft.) - minimum distance of 8 ft. is most effective and prevents spreading of burning material
- Discharge time (minimums): 2-1/2 lb. size (10 seconds), 5 lb. size (14 seconds), 10 lb. size (20 seconds) and 20 lb. size (30 seconds)

Item No.	Description
549973C91	2-1/2 lb. capacity - U/L Rating 1A-10B:C, Includes Vehicle Bracket*
549974C91	5 lb. capacity - U/L Rating 2A-10B:C, Includes Vehicle Bracket*
549975C91	10 lb. capacity - U/L Rating 4A-10B:C
KMB504765	20 lb. capacity - U/L Rating 20A-120B:C

* USCG approved with bracket



Item No.
549973C91

Item No.
549974C91

Item No.
549975C91

Item No.
KMB504765



Item No. KM700709200

Water Fire Extinguisher

Item No. KM700709200

- The cooling, soaking and penetrating 30-45 foot stream and 50-second discharge time make it a very effective and inexperienced-operator-friendly extinguisher for use on Class A fires
- 2-1/2 gallon capacity - U/L Rating 2A
- Stainless steel stored-pressure extinguisher
- Operating temperature: 40° F to 120° F
- Operating range: 45-55 ft.
- Operating time: 50 seconds



Item No. KM700709201

Mounting Brackets

Item No.	Holding Capacity
549978C91	10 lb.
KM700709201	20 lb. & 2-1/2 gal.