Printing date 04/22/2015 Revised On 04/22/2015

#### 1 Identification of the substance and manufacturer

WHITE LITHIUM GREASE Trade name:

DHJWOJ0001 **Product code:** Manufacturer/Supplier: Seymour of Sycamore 917 Crosby Avenue

Sycamore, IL 60178 Phone: 815-895-9101 www.seymourpaint.com CHEMTEL 1-800-255-3924, or 813-248-0585. **Emergency telephone number:** 

## 2 Hazard(s) identification

### Classification of the substance or mixture

Flam. Aerosol 1 H222 Extremely flammable aerosol.

H280 Contains gas under pressure; may explode if heated. Press. Gas

STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.

Eye Irrit. 2A H319 Causes serious eye irritation. STOT SE 3 H336 May cause drowsiness or dizziness

**GHS Hazard pictograms** 



Signal word Danger

Hazard statements Extremely flammable aerosol.

Contains gas under pressure; may explode if heated.

Causes serious eye irritation. May cause drowsiness or dizziness.

May cause damage to organs through prolonged or repeated exposure.

**Precautionary statements** Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use.

Wash hands thoroughly after handling.
Use only outdoors or in a well-ventilated area.

Wear protective gloves/protective clothing/eye protection/face protection. Do not breathe dust/fume/gas/mist/vapors/spray.

If INHALED: Remove person to fresh air and keep comfortable for breathing. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Call a poison center/doctor if you feel unwell. If eye irritation persists: Get medical advice/attention.

Store locked up.

Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F. Store in a well-ventilated place. Keep container tightly closed.

Dispose of contents/container in accordance with local/regional/national/international

regulations.

# 3 Composition/information on ingredients

**Chemical characterization: Mixtures** 

**Chemical Description:** This product is a mixture of the substances listed below with nonhazardous additions.

Dangerous components:	
64742-47-8 Mineral Spirits	52.0%
74-98-6 propane	12.6%
106-97-8 n-butane	7.4%

### 4 First-aid measures

After inhalation: Supply fresh air; consult doctor in case of complaints.

After skin contact: Remove contaminated clothing. Wash exposed area with soap and water.

After eye contact: Rinse opened eye for several minutes under running water.

Rinse mouth with water. Do not induce vomiting. After swallowing:

Most important symptoms and effects:

Indication of any immediate medical

Dizziness

attention needed: No further relevant information available.

### 5 Fire-fighting measures

**Extinguishing agents:** CO2, extinguishing powder or water spray. Fight larger fires with water spray.

Special hazards: Can form explosive gas-air mixtures. Protective equipment for

firefighters: A respiratory protective device may be necessary.

## 6 Accidental release measures

Personal precautions, protective

equipment and emergency

procedures: Use respiratory protective device against the effects of fumes/dust/aerosol. Methods and material for

containment and cleaning up: Absorb liquid components with liquid-binding material. Printing date 04/22/2015 Revised On 04/22/2015

Trade name: WHITE LITHIUM GREASE

(Contd. of page 1)

7 Handling and storage

Precautions for safe handling

Use only in well ventilated areas.

Keep away from sources of heat and direct sunlight. Do not warehouse in subfreezing Storage requirements:

conditions. Store locked up.

8 Exposure controls/personal protection

Components with limit values that require monitoring at the workplace:

74-98-6 propane

PEL (USA) Long-term value: 1800 mg/m³, 1000 ppm REL (USA) Long-term value: 1800 mg/m³, 1000 ppm

TLV (USA) refer to Appendix F

106-97-8 n-butane

REL (USA) Long-term value: 1900 mg/m<sup>3</sup>, 800 ppm TLV (USA) Short-term value: 2370 mg/m³, 1000 ppm

Hygienic protection: Wash hands after use.

Do not eat or drink while working.

**Breathing equipment:** A respirator is generally not necessary when using this product outdoors or in large open areas.

In cases where short and/or long term overexposure exists, a charcoal filter respirator should be worn. If you suspect overexposure conditions exist, please consult an authority on chemical

hygeine.

Hand protection: Protective gloves. The glove material must be impermeable and resistant to the substance.

Eye protection: Tightly sealed goggles

9 Physical and chemical properties

Appearance: Aerosol. Odor: Aromatic Odor threshold: Not determined. pH-value: Not determined Melting point/Melting range Undetermined. **Boiling point:** -44 °C (-47 °F)

-19 °C (-2 °F) Flash point: Flammability (solid, gas): Extremely flammable.

**Decomposition temperature:** Not determined.

Auto igniting: Product is not self-igniting.

Danger of explosion: In use, may form flammable/explosive vapour-air mixture.

**Lower Explosion Limit:** 0.5 Vol % **Upper Explosion Limit:** 10.9 Vol % Vapor pressure at 20 °C (68 °F): 2 hPa (2 mm Hg)

**Relative Density:** Between 0.77 and 0.85 (Water equals 1.00)

Vapour density Not determined. **Evaporation rate** Not applicable. Partition coefficient: n-octonal/water: Not determined. Not determined. Solubility: Viscosity: Not determined. **VOC** content: 720.0 g/l / 6.01 lb/gl

VOC content (less exempt solvents): 72.0 % Solids content: 28.0 %

10 Stability and reactivity

Stable at normal temperatures. Reactivity:

Conditions to avoid: Do not allow can to exceed 120 degrees Fahrenheit. Do not warehouse in subfreezing

temperatures.

Chemical stability: Not fully evaluated.

Possibility of hazardous reactions: No dangerous reactions known. Incompatible materials: No further relevant information available. Hazardous decomposition: No dangerous decomposition products known.

11 Toxicological information

LD/LC50 values that are relevant for classification:

106-97-8 n-butane

Inhalative LC50/4 h 658 mg/l (rat)

Information on toxicological effects: No data available. Skin effects: No irritant effect. Eye effects: No irritating effect.

Sensitization: No sensitizing effects known.

Carcinogenic categories

IARC (International Agency for Research on Cancer)

None of the ingredients is listed.

(Contd. on page 3)

(Contd. of page 2)

Printing date 04/22/2015 Revised On 04/22/2015

Trade name: WHITE LITHIUM GREASE

NTP (National Toxicology Program)

None of the ingredients is listed.

12 Ecological information

Hazardous for water, do not empty into drains.

Aquatic toxicity:
Persistence and degradability:

The product is degradable after prolonged exposure to natural weathering processes.

Bioaccumulative potential: Mobility in soil: Other adverse effects:

No further relevant information available. No further relevant information available. No further relevant information available.

13 Disposal considerations

Dispose of in accordance with local, state, and federal regulations. Do not puncture, incinerate, or compact. Partially empty cans must be disposed of responsibly. Do not heat or cut empty containers with electric or gas torches.

Recommendation: Completely empty cans should be recycled.

14 Transport information

**UN-Number** UN1950 DOT N/A

DOT Consumer Commodity ORM-D

Aerosols, flammable

**ADR** 1950 Aerosols

Transport hazard class(es):

Class 2.1 Marine pollutant: No

Warning: Gases F-D,S-U Special precautions for user:

**EMS Number:** 

**Quantity limitations** On passenger aircraft/rail: 75 kg On cargo aircraft only: 150 kg

**ADR** 

**Excepted quantities (EQ)** Code: E0

Not permitted as Excepted Quantity

**IMDG** 

Limited quantities (LQ)

Excepted quantities (EQ) Code: E0 Not permitted as Excepted Quantity

Packaging Group: UN "Model Regulation":

UN1950, Aerosols, 2.1

15 Regulatory information

SARA Section 355 (extremely hazardous substances):

None of the ingredients in this product are listed

SARA Section 313 (Specific toxic chemical listings):

None of the ingredients is listed.

CPSC: This product complies with 16 CFR 1303 and does not contain more than 90 ppm of lead.

California Proposition 65 chemicals known to cause cancer:

None of the ingredients in this product are listed.

**CANADIAN ENVIRONMENTAL** 

**PROTECTION ACT:** All hazardous ingredients for this product appear on the Canadian Domestice Substance List.

EPA:

None of the ingredients is listed.

16 Other information

Contact: Regulatory Affairs Date of preparation / last revision 04/22/2015 / -